

BALDOR® • RELIANCE

Product Information Packet

VL1205A

.33HP,3450RPM,1PH,60HZ,56C,3416L,OPEN,F1

Part Detail							
Revision:	G	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3416L	Elec. Spec:	34WG0652	CD Diagram:	CD0052
Enclosure:	OPEN	Mfg Plant:		Mech. Spec:	34F037	Layout:	34LYF037
Frame:	56C	Mounting:	F1	Poles:	02	Created Date:	02-22-2010
Base:	N	Rotation:	ROS	Insulation:	B	Eff. Date:	06-03-2015
Leads:	6#18,1#16 #1TH					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1257L

CAT.NO.	VL1205A									
SPEC.	34F037-0652G1									
HP	.33									
VOLTS	115/230									
AMP	7/3.5									
RPM	3450									
FRAME	56C				HZ 60				PH 1	
SER.F.	1.75		CODE P		DES N		CL B			
NEMA-NOM-EFF	54		PF 56							
RATING	40C AMB-CONT									
CC			USABLE AT 208V							
DE	6203		ODE 6203							
ENCL	OPEN		SN							
	SFA 8.2/4.1									

Parts List		
Part Number	Description	Quantity
SA191204	SA 34F037-0652G1	1.000 EA
RA178865	RA 34F037-0652G1	1.000 EA
EC1270A02SP	ELEC CAP, 270-324 MFD, 125V, 1.48D X 3.	1.000 EA
34EP3202A03	FR ENDPLATE, MACH	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	3.000 EA
11XT0832G06	8-32 X 3/8 TY 23 TAPPING	1.000 EA
WD4100A01	DP-875 HEYCO PLUG OR 62MP0875 MICRO PLAS	1.000 EA
NS2500A01	INSULATOR, AUTO THER PROT	1.000 EA
34CB4800SP	CAPACITOR COVER, STAMPED PRIMED	1.000 EA
51XB1016A05	10-16X5/16HX WA SL SR TYB (F/S)	2.000 EA
HW5100A03	WAVY WASHER (W1543-017)	1.000 EA
34EP3401A01SP	PU ENDPLATE, MACH	1.000 EA
34AD2000	BAFFLE PLATE, STAMPED	1.000 EA
51XT0632A06	6-32X3/8 TY23 HXWS SLDSR	4.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
34FH4500A02P	DRIPCOVER, MODEL 34	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
34CB4501SP	TERMINAL BOX LID, STAMPED X (PLATED)	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
HW2501D13	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
MG1000G27	MED CHARCOAL METALLIC GREY 400-0096	0.014 GA
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA
SP5068A04	MODEL 34 TERMINAL PANEL SWITCH WITH LEAD	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
HA3100A14	THRUBOLT 10-32 X 7.875	4.000 EA
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 EA
LC0052	CONNECTION LABEL	1.000 EA
NP1257L	ALUM UL CSA CC THERMAL REV MTG	1.000 EA
35PA1000	PKG GRP, PRINT PK1008A06	1.000 EA
PK3083T	STYROFOAM PACKING CRADLE W/TAPE	1.000 EA

AC Induction Motor Performance Data

Record # 36344 - Typical performance - not guaranteed values

Winding: 34WG0652-R002	Type: 3416L	Enclosure: OPEN
-------------------------------	--------------------	------------------------

Nameplate Data				115 V, 60 Hz: Low Voltage Connection	
Rated Output (HP)	.33			Full Load Torque	0.489 LB-FT
Volts	115/230			Start Configuration	direct on line
Full Load Amps	7/3.5			Breakdown Torque	2 LB-FT
R.P.M.	3450			Pull-up Torque	1.6 LB-FT
Hz	60	Phase	1	Locked-rotor Torque	3 LB-FT
NEMA Design Code	N	KVA Code	P	Starting Current	37 A
Service Factor (S.F.)	1.75			No-load Current	5.9 A
NEMA Nom. Eff.	54	Power Factor	56	Line-line Res. @ 25°C	1.15 Ω A Ph 3.67 Ω B Ph
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	67°C
S.F. Amps	8.2/4.1			Temp. Rise @ S.F. Load	89°C

Load Characteristics 115 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	43	50	56	61	67	72
Efficiency	28.6	40.1	48.9	53.8	56	56.8	60
Speed	3538	3507	3478	3460	3434	3412	3388
Line amperes	5.93	6.17	6.53	6.99	7.54	8.08	8.43

Performance Graph at 115V, 60Hz, 0.33HP Typical performance - Not guaranteed values





