

BALDOR® • RELIANCE

Product Information Packet

CEM31107

.5HP,3450RPM,3PH,60HZ,56C,3416M,OPEN,F1

Part Detail							
Revision:	B	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3416M	Elec. Spec:	34WGS937	CD Diagram:	CD0005
Enclosure:	OPEN	Mfg Plant:		Mech. Spec:	34F010	Layout:	34LYF010
Frame:	56C	Mounting:	F1	Poles:	02	Created Date:	09-30-2014
Base:	RG	Rotation:	R	Insulation:	B	Eff. Date:	09-26-2016
Leads:	9#18					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP3155L

CAT.NO.	CEM31107													
SPEC.	34F010S937G1													
HP	.5													
VOLTS	230/460													
AMP	1.6/.8													
RPM	3450													
FRAME	56C					HZ		60					PH	3
SER.F.	1.25			CODE		P		DES		B		CL		B
F.L. AVG. EFF.	73.4				PF		78							
RATING	40C AMB-CONT													
CC					USABLE AT 208V									1.9
DE	6203					ODE		6203						
ENCL	OPEN			SN										
	SFA 1.8/.9													

Parts List		
Part Number	Description	Quantity
SA287921	SA 34F010S937G1	1.000 EA
RA274124	RA 34F010S937G1	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
34CB3002A	CB CAST W/.88 DIA HOLE	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
34EP3210A01SP	FR ENDPLATE, MACH	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
34EP3401A01SP	PU ENDPLATE, MACH	1.000 EA
34AD2000	BAFFLE PLATE, STAMPED	1.000 EA
51XT0632A06	6-32X3/8 TY23 HXWS SLDSR	4.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
34CB4517	CB LID 4 MTG HOLES .22 DIA STAMPED, FOR	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW2501D13	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
MG1000Y03	MUNSELL 2.53Y 6.70/ 4.60, GLOSS 20,	0.014 GA
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA
HA3100A12	THRUBOLT 10-32 X 7.375	4.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1000/bx) 11/14	1.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119N)	1.000 EA
NP3155L	ALUM SUPER-E UL CSA CC "SEMS"	1.000 EA
35PA1000	PKG GRP, PRINT PK1008A06	1.000 EA

AC Induction Motor Performance Data

Record # 47468 - Typical performance - not guaranteed values


Winding: 34WGS937-R002	Type: 3416M	Enclosure: OPEN
-------------------------------	--------------------	------------------------

Nameplate Data				460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	.5			Full Load Torque	0.767 LB-FT
Volts	230/460			Start Configuration	direct on line
Full Load Amps	1.6/.8			Breakdown Torque	4.81 LB-FT
R.P.M.	3450			Pull-up Torque	3.29 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	4.44 LB-FT
NEMA Design Code	B	KVA Code	P	Starting Current	7.88 A
Service Factor (S.F.)	1.25			No-load Current	0.48 A
NEMA Nom. Eff.	73.4	Power Factor	78	Line-line Res. @ 25°C	22.08 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	15°C
S.F. Amps	1.8/.9			Temp. Rise @ S.F. Load	17°C
				Locked-rotor Power Factor	66
				Rotor inertia	0.0148 LB-FT ²

Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	61	72	78	83	86	83
Efficiency	54	67.8	73.9	76.9	78.3	78.8	78.3
Speed	3560	3537.1	3511.5	3484.8	3456.5	3427.6	3456
Line amperes	0.524	0.591	0.676	0.79	0.911	1.05	0.911

Performance Graph at 460V, 60Hz, 0.5HP Typical performance - Not guaranteed values



AC Induction Motor Performance Data

Record # 49386 - Typical performance - not guaranteed values

Winding: 34WGS937-R002	Type: 3416M	Enclosure: OPEN
-------------------------------	--------------------	------------------------

Nameplate Data				230 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	.5			Full Load Torque	0.767 LB-FT
Volts	230/460			Start Configuration	direct on line
Full Load Amps	1.6/.8			Breakdown Torque	4.81 LB-FT
R.P.M.	3450			Pull-up Torque	3.29 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	4.44 LB-FT
NEMA Design Code	B	KVA Code	P	Starting Current	15.76 A
Service Factor (S.F.)	1.25			No-load Current	0.96 A
NEMA Nom. Eff.	73.4	Power Factor	78	Line-line Res. @ 25°C	5.52 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	15°C
S.F. Amps	1.8/.9			Temp. Rise @ S.F. Load	17°C
				Locked-rotor Power Factor	66
				Rotor inertia	0.0148 LB-FT ²

Load Characteristics 230 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	61	72	78	83	85	83
Efficiency	54	67.8	73.9	76.9	78.3	78.8	78.3
Speed	3560	3537.1	3511.5	3484.8	3456.5	3427.6	3456
Line amperes	1.048	1.182	1.352	1.58	1.822	2.1	1.822

Performance Graph at 230V, 60Hz, 0.5HP Typical performance - Not guaranteed values

