

BALDOR® • RELIANCE

Product Information Packet

CSSEWDM3537-5

.5HP,3500RPM,3PH,60HZ,56C,3516M,TENV,F1

Part Detail							
Revision:	P	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3516M	Elec. Spec:	35WGN872	CD Diagram:	CD0006
Enclosure:	TENV	Mfg Plant:		Mech. Spec:	35Z189	Layout:	35LYZ189
Frame:	56C	Mounting:	F1	Poles:	02	Created Date:	02-07-2013
Base:	RG	Rotation:	R	Insulation:	H	Eff. Date:	03-02-2017
Leads:	3#18 Dbl Dip & Bake,0#0 Phase Insulate,0#0 15" LEAD LENGY					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP2922A05

CAT.NO.	CSSEWDM3537-5											
SPEC.	35Z189N872G1											
HP	.5											
VOLTS	575											
AMP	.6											
RPM	3500											
FRAME	56C				HZ			60		PH	3	
SER.F.	1.15			CODE		N	DES		B	CLASS		H
NEMA-NOM-EFF	84				PF		84					
RATING	40C AMB-CONT											
CC					USABLE AT 208V							
DE	6205				ODE		6205					
ENCL	TENV			SN								

Parts List		
Part Number	Description	Quantity
SA258347	SA 35Z189N872G1	1.000 EA
RA245120	RA 35Z189N872G1	1.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
35FE1917A10	FREP TENV 205 BRG NO GRS 4X.125 NPT (SS)	1.000 EA
RM1070A25	O-RING, VITON/FKM .070CS X 6.190ID	1.000 EA
HW4500A33	1/8 NPT STAINLESS,HOLO-KROME #13002,PRES	3.000 EA
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA
35PE1916A05	PUEP 56C ENC 205 BRG 4X.125 NPT (SS)	1.000 EA
RM1070A25	O-RING, VITON/FKM .070CS X 6.190ID	1.000 EA
HW4600E99	AXIAL FACE SEAL 76925-9042-0447 SS CASE	1.000 EA
HW4500A33	1/8 NPT STAINLESS,HOLO-KROME #13002,PRES	3.000 EA
RM1070A26	O-RING,4.5MM I.D.X1.5MM C.S. (VITON)	4.000 EA
36GS3008SP	WHITE NEOPREME KO BOX LID GASKET	1.000 EA
35CB4515	35 CB LID #304 STAINLESS STEEL	1.000 EA
59XN0832S07	8/32 X 7/16 HX WS HD SER X	4.000 EA
HW2502D13	SS KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.005 QT
MJ5004A37	#76732 LOCTITE ANTISEIZE THRD COMPOUND	0.005 EA
HA5027A02	HA4054 T-DRAIN X2 BAGGED WITH LABEL	1.000 EA
MJ1000A02	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
WD5603A02	KIT, CLOSED-END LEAD SPLICE (18-14GA)	1.000 EA
HA3100S01	THRUBOLT- 10-32 X 8.187 302 OR 303 SS	4.000 EA
36PA1000	PKG GRP, PRINT PK1016A06	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
MN416A01	TAG-INSTAL-MAINT no wire (1000/bx) 11/14	1.000 EA
HA5027A07	85XU1208S08 FACE DRAIN PINS BAGGED	1.000 EA

AC Induction Motor Performance Data

Record # 41246 - Typical performance - not guaranteed values


Winding: 35WGN872-R001	Type: 3516M	Enclosure: TENV
-------------------------------	--------------------	------------------------


Nameplate Data				575 V, 60 Hz: Single Voltage Motor	
Rated Output (HP)	.5			Full Load Torque	0.758 LB-FT
Volts	575			Start Configuration	direct on line
Full Load Amps	.6			Breakdown Torque	3.91 LB-FT
R.P.M.	3500			Pull-up Torque	1.65 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	3.18 LB-FT
NEMA Design Code	B	KVA Code	N	Starting Current	5.93 A
Service Factor (S.F.)	1.15			No-load Current	0.323 A
NEMA Nom. Eff.	84	Power Factor	84	Line-line Res. @ 25°C	39.4 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	46°C
S.F. Amps				Temp. Rise @ S.F. Load	52°C
				Locked-rotor Power Factor	55
				Rotor inertia	0.0443 LB-FT ²

Load Characteristics 575 V, 60 Hz, 0.5 HP


% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	41	60	72	80	85	88	83
Efficiency	71.9	80.2	83.3	84.6	84.7	84	84.7
Speed	3573	3552	3528	3502	3477	3449	3487
Line amperes	0.347	0.398	0.47	0.56	0.657	0.763	0.618

Performance Graph at 575V, 60Hz, 0.5HP Typical performance - Not guaranteed values





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: D

BY: JLP

REVISED: 01/21/99 4:02

TDR: 0171435

9000D

FILE: AAA00005141

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

CD0006